

The logo for encapsulite, featuring the word "encapsulite" in a white, lowercase, sans-serif font. Above the text is a decorative graphic of a series of yellow dots arranged in a curved, arc-like pattern.

encapsulite

# 24V RD TWIN STICK IP64

REMOTE DRIVER





## Suspended/Surface mounted. Tubular diffused light, with black IP64 end caps.

### THE LATEST LED CHIPS CREATE A CLEANER LIGHT OUTPUT.

The 24V RD Twin Stick is a robust, slim LED diffused cylindrical tube with the latest LED chips creating a cleaner 360° light output. The fitting can be suspended horizontally, vertically or at any angle, as well as surface mounted. Ideal as a creative feature luminaire.

The 24V RD Twin Stick IP64 will operate from a 24V constant voltage driver and can be dimmable.

Suitable for almost any dry exterior application.

#### Light Source Information

- LED/Electronic Driver.
- Available in 2700K, 3000K & 4000K.

#### Options

- Black end caps only.

#### Dimming

Leading/trailing edge, Dali, 1-10V. Driver must be installed in a dry place or can be supplied in 70mm casing for external use.

#### Installation

Horizontal, vertical, angled suspension or surface mounted.

#### Optics

Satin polycarbonate diffuser.

Cat No.	Length (mm)	Illuminated Length (mm)	Lumens	Circuit Power (W)
24V RD TS WP 5	600	480	480	11
24V RD TS WP 10	1095	970	1015	19
24V RD TS WP 15	1600	1470	1450	27



End Cap



Suspension Kit



Polycarbonate clips

#### For further information

Call: +44 (0)1525 376974

Email: [reply@encapsulite.co.uk](mailto:reply@encapsulite.co.uk)

or visit [www.encapsulite.co.uk](http://www.encapsulite.co.uk)



Tube ø 30mm



Cap ø 34mm



Light output 360°